

ref. 99028511

# PUSH-UP LADDER B PART 2,7M EN1147

## REDDINGSLADDERS

DESCRIPTION

Scaling ladder part B made of aluminium with red heat-insulating and grip-proof protective cover. The footrests have a good anti-slip property. Lock pins with spring in galvanised steel. Complies with EN1147.

Part B fits into the plug-in ladder part A (ref. 99016553).

TECHNICAL SPECIFICATIONS

- Rescue height: 1 600 mm
- Ladder length: 2 700 mm
- Ladder length 4 plug-in ladders: 8 400 mm
- Number of steps/rungs: 7
- Max load: 216 kg
- Max number of persons: 2
- Weight: 9.8 kg
- Angle of attack: 70°
- Width: 575 mm
- Side height: 74 mm
- Width rung: 35 mm
- Height rung: 28 mm
- Depth rung: 29 mm
- Distance between rungs: 273 mm
- Ladder feet: Interchangeable non-slip ladder shoe
- Material: aluminium
- Sports material: aluminium with heat-insulating non-slip plastic coating
- Corrosion-resistant fittings made of galvanised steel
- Standardisation: EN 1147

ACCESSORIES AND OPTIONS

- 99028512: Plug-in ladder part B alu EN1147
- 99016553: Pitch ladder 2.7m part A EN1147

**Vanassche Firefighting Engineering**
Brugsesteenweg 8
B-8531 Harelbeke
+32 (0) 56 710 130
info@vanassche-fire.be
BE 0415.345.684
RPR Gent - Afdeling Kortrijk
vanassche-fire.be

**Vanassche Services**
Brugsestraat 153
B-8531 Harelbeke
+32 (0) 56 738 188
services@vanassche-fire.be
BE 0473.397.315
RPR Gent - Afdeling Kortrijk
vanassche-fire.be

- 99039314: anti-slip repair kit for ladder step
- 99066703: Ladder base red
- 99044563: aluminium sports profile
- Adjustable foot extension
- Ladder connecting part
- Plug pocket
- Ladder lock





**Vanassche Firefighting Engineering**
Brugsesteenweg 8
B-8531 Harelbeke
+32 (0) 56 710 130
info@vanassche-fire.be
BE 0415.345.684
RPR Gent - Afdeling Kortrijk
vanassche-fire.be

**Vanassche Services**
Brugsestraat 153
B-8531 Harelbeke
+32 (0) 56 738 188
services@vanassche-fire.be
BE 0473.397.315
RPR Gent - Afdeling Kortrijk
vanassche-fire.be