

ref. 99028512

PUSH-UP PART ALU EN1147

REDDINGSLADDERS

Ladder length: 780 mm

Number of rungs: 2

Weight: 3 kg

Max load: 216 kg

Ladder feet: Interchangeable non-slip ladder shoe

Suitable for side ladder 2.7m part B EN1147 (ref. 99028511)

DESCRIPTION

Push-fit section fitting in lower part of push-fit ladder part B (ref. 99028511) to make complete ladder.

TECHNICAL SPECIFICATIONS

- Ladder length: 780 mm
- Number of rungs: 2
- Max load: 216 kg
- Max number of persons: 2
- Weight: 3 kg
- Angle of attack: 70°
- Width: 485 mm
- Side height: 74 mm
- Width rung: 35 mm
- Height rung: 28 mm
- Depth rung: 29 mm
- Distance between rungs: 273 mm
- Ladder feet: Interchangeable non-slip ladder shoe
- Material: aluminium
- Sports material: aluminium with heat-insulating non-slip plastic coating
- Corrosion-resistant fittings made of galvanised steel
- Standardisation: EN 1147
- Suitable for side ladder 2.7m part B EN1147 (ref. 99028511)

Vanassche Firefighting Engineering
Brugsesteenweg 8
B-8531 Harelbeke
+32 (0) 56 710 130
info@vanassche-fire.be
BE 0415.345.684
RPR Gent - Afdeling Kortrijk
vanassche-fire.be

Vanassche Services
Brugsestraat 153
B-8531 Harelbeke
+32 (0) 56 738 188
services@vanassche-fire.be
BE 0473.397.315
RPR Gent - Afdeling Kortrijk
vanassche-fire.be





Vanassche Firefighting Engineering
Brugsesteenweg 8
B-8531 Harelbeke
+32 (0) 56 710 130
info@vanassche-fire.be
BE 0415.345.684
RPR Gent - Afdeling Kortrijk
vanassche-fire.be

Vanassche Services
Brugsestraat 153
B-8531 Harelbeke
+32 (0) 56 738 188
services@vanassche-fire.be
BE 0473.397.315
RPR Gent - Afdeling Kortrijk
vanassche-fire.be