

ref. 99023013

ALUMINIUM HOOK LADDER 4,4M EN1147

HAAKLADDERS

Ladder length: 4 400 mm

Weight: 11.5 kg

Max load: 150 kg

Ladder feet: Interchangeable non-slip ladder shoe

DESCRIPTION

Hook ladder with folding bracket with small sharp points and edge hook. Wall brackets are welded on as standard and the 10 rungs are equipped with a plastic heat-insulating covering. Complies with standard EN1147.

TECHNICAL SPECIFICATIONS

- Hook ladder
- Ladder length: 4 400 mm
- Number of rungs : 10
- Max load: 150 kg
- Max number of persons: 1
- Weight: 11,5 kg
- Width: 300 mm
- Clear width: 250 mm
- Side height: 60 mm
- Width rung: 25 mm
- Height rung: 28 mm
- Depth rung: 29 mm
- Distance between rungs: 335 mm
- Ladder feet: Interchangeable non-slip ladder shoe
- Material: aluminium
- Material steps: aluminium with heat-insulating anti-slip plastic coating
- Corrosion-resistant fittings made of galvanised steel
- Foldable hook made of galvanised steel, secured with a locking pin
- Standardisation: EN 1147

Vanassche Firefighting Engineering
Brugsesteenweg 8
B-8531 Harelbeke
+32 (0) 56 710 130
info@vanassche-fire.be
BE 0415.345.684
RPR Gent - Afdeling Kortrijk
vanassche-fire.be

Vanassche Services
Brugsestraat 153
B-8531 Harelbeke
+32 (0) 56 738 188
services@vanassche-fire.be
BE 0473.397.315
RPR Gent - Afdeling Kortrijk
vanassche-fire.be

ACCESSORIES

- replaceable step
- repair kit steps covering







Vanassche Firefighting Engineering
Brugsesteenweg 8
B-8531 Harelbeke
+32 (0) 56 710 130
info@vanassche-fire.be
BE 0415.345.684
RPR Gent - Afdeling Kortrijk
vanassche-fire.be

Vanassche Services
Brugsestraat 153
B-8531 Harelbeke
+32 (0) 56 738 188
services@vanassche-fire.be
BE 0473.397.315
RPR Gent - Afdeling Kortrijk
vanassche-fire.be