

ref. 99014985

CMM-ALU-DSP LANCE

STRAALPIJPEN DIVERS

Easy to operate

Flow rate: 130-230 l/min ((at 6 bar), with water curtain 290-400 l/min

Valve type: ball valve with three positions: closed, full jet, spray jet

With man protection

TECHNICAL SPECIFICATIONS

- Flow rate: 130-230 l/min ((at 6 bar), with water curtain 290-400 l/min
- Pressure Pn: 16 bar
- Unscrewable nozzle diameter 9 mm
- Pipe mouth diameter: 12 mm
- Type of valve: ball valve with three positions: closed, full jet, spray jet
- Man protection: water curtain, can be opened separately via the swivel ring at the front of the nozzle
- Spray angle of 15-20°, with water curtain up to 160°
- Throw length: 27 m (full jet), 13 m (spray jet)
- Coupling: DSP 45 without bolt
- Dimensions: L445 x W90 x H165 mm
- Material: aluminium
- Standardisation: EN15182-3
- Weight: 1.7 kg



Vanassche Firefighting Engineering
Brugsesteenweg 8
B-8531 Harelbeke
+32 (0) 56 710 130
info@vanassche-fire.be
BE 0415.345.684
RPR Gent - Afdeling Kortrijk
vanassche-fire.be

Vanassche Services
Brugsestraat 153
B-8531 Harelbeke
+32 (0) 56 738 188
services@vanassche-fire.be
BE 0473.397.315
RPR Gent - Afdeling Kortrijk
vanassche-fire.be